

EPD

Environmental Product Declaration

ABB Earthing Truck DY507

Production site: Dalmine, Italy



DOCUMENT KIND Environmental Product Declaration	IN COMPLIANCE WITH ISO 14025 and EN50693			
PROGRAM OPERATOR EPDItaly	PUBLISHER EPDItaly			
EPDITALY REGISTRATION NUMBER EODITALY0197	ISSUE DATE 2021-11-02			
VALID TO 2026-11-02	STATUS Approved	SECURITY LEVEL Internal		
OWNING ORGANIZATION ABB S.p.A.	DECLARATION NUMBER 2RDA042901	REV. A	LANG. en	PAGE 1/17

EPD Owner	ABB S.p.A.
Manufacturer name and address	ABB S.p.A. Via Friuli, 4, 24044 Dalmine (BG)
Company contact	Stefano Vitali - stefano.vitali@it.abb.com R&D Manager - Field Application Support
Program operator	EPDItaly – info@epditaly.it via Gaetano De Castillia n° 10 - 20124 Milano, Italia
Declared product & Functional unit or declared unit	Earthing Truck DY507 FU: single earthing truck, which measures and detect the busbars voltage, during a service of 20 years, including the packaging.
Product description	The earthing trucks are mainly used as safety apparatus during grid maintenance, ensuring a low resistance connection to earth of medium voltage busbars.
CPC code	46211 - Electrical apparatus for switching or protecting electrical circuits, or for making connexions to or in electrical circuits, for a voltage exceeding 1000 V
Independent verification	This declaration has been developed referring to EPDItaly, following the "Regolamento di EPDItaly"; further information and the document itself are available at: www.epditaly.it . EPD document valid within the following geographical area: Italy and other countries worldwide according to sales market conditions Independent verification of the declaration and data carried out according to ISO 14025: 2010. <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL Third party verification carried out by: ICMQ spa Accredited by: ACCREDIA
Reference PCR and version number	Core PCR: EPDItaly007 – PCR for Electronic and Electrical Products and Systems, Rev. 2, 2020/10/21.
Other reference documents	EN 50693:2019 - Product category rules for life cycle assessments of electronic and electrical products and systems Regulations of the EPDItaly Programme rev. 5.0 (1st July 2020)
Product RSL description	20 years
Markets of applicability	World (raw materials), Italy (production, use and end-of-life)
LCA study	This EPD is based on the LCA study described in the LCA report 2RDA042904.
EPD type	Product specific
EPD scope	"Cradle to grave"
Year of reported primary data	2020
Technical support	2B Srl (Italy) Via della Chiesa Campocroce 4, Mogliano Veneto (TV)
LCA software	SimaPro 9.1.1 (2020)
LCI database	ecoinvent v3.6 (2019)
LCIA methodology	EN 50693:2019

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	2/17

Comparability	EPDs published within the same product category, though originating from different programs, may not be comparable. Full conformance with a PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible.
Liability	EPDItaly declines any responsibility regarding the manufacturer's information, data and results of the life cycle assessment.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	3/17

Contents

ABB Purpose & Embedding Sustainability.....5

General Information..... 6

Constituent materials7

LCA background information 8

Inventory analysis12

Environmental indicators.....14

Additional environmental information.....16

References 17

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	4/17



ABB Purpose & Embedding Sustainability

ABB is a leading global technology company that energizes the transformation of society and industry to achieve a more productive, sustainable future. By connecting software to its electrification, robotics, automation and motion portfolio, ABB pushes the boundaries of technology to drive performance to new levels. With a history of excellence stretching back more than 130 years, ABB's success is driven by about 110 thousand talented employees in over 100 countries.

ABB's Electrification business offers a wide-ranging portfolio of products, digital solutions and services, from substation to socket, enabling safe, smart and sustainable electrification. Offerings encompass digital and connected innovations for low and medium voltage, including EV infrastructure, solar inverters, modular substations, distribution automation, power protection, wiring accessories, switchgear, enclosures, cabling, sensing and control.

ABB is committed to continually promoting and embedding sustainability across its operations and value chain, aspiring to become a role model for others to follow. With its ABB Purpose, ABB is focusing on reducing harmful emissions, preserving natural resources and championing ethical and humane behavior.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	5/17



General Information

ABB S.p.A Electrification Distribution Solutions facility in Dalmine (ABB IT-ELDS) produces medium voltage switches, disconnectors, and contactors, medium voltage switchboards for primary and secondary distribution, low voltage switchboards, complete packages and services for substations. Smart systems and technologies for electrical distribution are supplied to utilities, industrial, and tertiary sector customers. Dalmine exports 85% of the volumes produced.

ABB IT-ELDS adopts and implements for its own activities an integrated Quality/Environmental/Health Management System in compliance with the following standards:

- UNI EN ISO 9001/2015 - Quality Management Systems- Requirements
- UNI EN ISO 14001/2015 - Sistemi di Gestione Ambientale Requisiti e Guida per l'Uso
- BS OHSAS 18001/2007 - Occupational Health and Safety Assessment Series

The manufacturing of the Medium Voltage Earthing Truck (DY507) is located in ABB facility of Dalmine, Italy.

In the factory, the different components and subassemblies are assembled on the so called One Primary Line. All components and subassemblies are produced by ABB's suppliers and are only assembled in the factory.

Product cluster Medium Voltage Earthing Truck DY507 is declared in this LCA.

Technical information	
Medium voltage earthing truck	Earthing Truck DY507
Short time withstand current [kA]	12.5
Short time withstand duration [s]	1

The accessories associated with these products are also included in the study.


STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	6/17



Constituent materials

The Earthing Truck weighs almost 187.4 kg but small metal parts (e.g. screws) are not included in the analysis due to their limited weight (0.7% of the total mass). This is in line with the cut-off criteria of the PCR EDPltaly 012 (2%) and the EN 50693 standard (5%). Without small metal parts the total mass considered for the Earthing Truck DY507 is 185.97 kg.

Earthing Truck DY507				
Materials	Name	CAS Number	Weight [kg]	%
Plastics	Plastics and rubbers	-	0.24	0.1
Metals	Steel	68316-05-2	171.61	91.6
	Copper	7440-50-8	14.08	7.5
	Aluminium	7429-90-5	0.04	0.02
Others	Others	-	1.39	0.7
Total			187.4	100



The packaging is composed of steel fixing brackets, a wooden cage and a wooden pallet, resulting in a total weight of almost 25 kg.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	7/17



LCA background information

Functional Unit

The functional unit is a single earthing truck, which measures and detect the busbars voltage, during a service of 20 years, including related accessories and packaging.

System Boundaries

The life cycle of the Earthing Truck, an EEPS (Electronic and Electrical Products and Systems), is a “from cradle to grave” analysis and covers the following main life cycle stages: manufacturing, including the relevant upstream process (e.g. acquisition of raw material, preparation of semi-finished goods, etc.) and the main manufacturing and processing steps; distribution; installation, including the relevant steps for the preparation of the product for use; use including the required maintenance steps within the RSL (reference service life of the product) associated to the reference product; end-of-life stage, including the necessary steps until final disposal or recovery of the product system.

The following table shows the stages of the product life cycle and the information stages according to EN 50693 for the evaluation of electronic and electrical products and systems.


UPSTREAM	CORE	DOWNSTREAM			
Manufacturing		Distribution	Installation	Use	End-of-Life (EoL)
Acquisition of raw materials	Assembly EoL treatment of generated waste	Transport to distributor/ logistic center	Installation	Usage	De-Installation
Transport to manufacturing site		Reconditioning at distributor/ logistic center		EoL treatment of generated waste (packaging)	Maintenance
Components/parts manufacturing		Transport to place of use		EoL treatment of generated waste	EoL treatment
Packaging					

The stages of the product life cycle and the information considered for the evaluation of the cluster Earthing Truck DY507 are:

- Manufacturing upstream includes raw materials, and production activities of ABB suppliers, including transport of semifinished items and subassemblies to ABB Dalmine. This includes also the packaging production.
- The core part of the manufacturing stage includes local consumptions (ABB Dalmine), the relevant assembling and waste due to manufacturing.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	8/17

- The distribution stage includes the impacts related to the distribution of the product at the installation site.
- The installation stage includes the end of life of the packaging.
- The use and maintenance stages include the impact related to energy consumption during the service life of the product.
- End of life includes the operations for the disposal of the product at the end of its service life.



Temporal and geographical boundaries

The ABB component suppliers are sourced all over the world: Africa, Asia and Europe. All primary data collected from ABB are from 2020, which is a representative production year. Secondary data are also representative for this year, as provided by ecoinvent v3.6.

The selected ecoinvent processes in the LCA model have a global representativeness, due to the unclear origin of each component. In this way, a conservative approach has been adopted.

Boundaries in the life cycle

Capital goods, such as buildings, machinery, tools and infrastructure, the packaging for internal transport which cannot be allocated directly to the production of the reference product, may be excluded from the system boundary.

Infrastructures, when present, such as processes deriving from the ecoinvent database have not been excluded.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	9/17

Data quality

In this EPD, both primary and secondary data are used. Site specific foreground data have been provided by ABB. Main data sources are the bill of materials available on the enterprise resource planning. For all processes for which primary are not available, generic data originating from the ecoinvent v3.6 database, allocation cut-off by classification, are used. The ecoinvent database is available in the SimaPro 9.1.1 software used for the calculations.

Environmental impact indicators

The information obtained from the inventory analysis is aggregated according to the effects related to the various environmental issues. According to PCR EPDItaly007 and EN 50693 the environmental impact indicators must be determined using the characterization factors and impact assessment methods specified in EN 15804:2012+A2:2019.

PCR EPDItaly007 and the EN 50693 standard establish four indicators for climate impact (GWP-GHG): GWP (total) which includes all greenhouse gases; GWP (fossil fuels); GWP (biogenic carbon) which includes the emissions and absorption of biogenic carbon dioxide and biogenic carbon stored in the product; GWP (land use).

Allocation rules

An allocation key is used for consumptions related to the manufacturing process in the production site, as well for company waste. Since the factory produces several products (apparatus and switchgear), only a part of the environmental impact has been allocated to the production line.

Allocation coefficients are based on installed power for electricity and on the line's surface area for methane and water consumption. Company consumption is allocated to the OPL (One Primary Line) and divided by the total number of earthing trucks produced in 2019.

Concerning end-of-life allocation, the "cut-off" approach has been applied. As a result, the ecoinvent database "allocation, cut-off by classification" has been applied. With this approach, outputs subject to recycling are considered as inputs to the next life cycle, and neither environmental burdens nor environmental gains deriving from the recycling process are allocated to the waste stream.

Limitations and simplifications

The raw material life cycle stage includes the extraction of raw materials but neglects the production of various components at ABB's suppliers (fastener, other parts with very low weight), as their mass represent less than 2% of that of the whole earthing truck, as stated in the paragraph of cut-off criteria of EPDItaly012: "Materials making up

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	10/17

the switch itself whose total mass does not exceed 2% of the total weight of the device”.

This same applies for packaging, where small parts such as screws and fasteners are even a smaller fraction of the total mass.

Also sticking labels and grease have been excluded since they are negligible.

Surface treatments like galvanizing, tin plating, silver plating and painting have been considered in the LCA model. Phosphated surface treatments have been excluded by operational choice.

Scraps for metal working and plastic processes are included when already defined inecoinvent.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	11/17



Inventory analysis

Theecoinvent v3.6 cut-off by classification system processes are used to model the background system of the processes.

Due to the large amounts of components in the Earthing Truck, raw material inputs are modelled with data from ecoinvent representing a global market coverage. These datasets are assumed to be representative.

Manufacturing stage

Steel is the most frequently used material, followed by copper. All steel components (hot rolled, cold rolled, galvanized, low-alloyed steel) are modelled with the same kind of steel: “Steel, low-alloyed [GLO] market for”, as it is representative for the large majority of the steel parts.

The single use packaging is also included in the analysis in the manufacturing stage-core. ABB receives packaging components from outside suppliers and packages the trucks before shipping them.

The transport distances from raw materials suppliers to the manufacturing are assumed to be 300 km. The distance from subassembly manufacturing factory to ABB facility is calculated.

The manufacturing of the Earthing Truck takes place in ABB facility of Dalmine, Italy. In the factory, the different components and subassemblies are assembled into the earthing truck.

The energy mix used for the production phase is representative for Dalmine production site and includes green energy only (hydroelectric 79%, wind 8% and photovoltaic 13%).

The waste generated by the production and assembly processes is included in the calculation.

Distribution

The transport distances from ABB plant to the place of use are assumed to be 300 km.

Installation

The installation phase only implies manual activities and no energy is consumed. This phase also includes the disposal of the packaging of the earthing truck.

Use

Use and maintenance are modelled according to the PCR EPDIItaly007.

Medium voltage earthing truck can be inserted or extracted in order to fulfil its purpose. Insertion and extraction operations can be only made with network disconnected. For this

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	12/17

reason, no electricity dissipation occurs in a normal earthing truck life. Additionally, since no maintenance happens during the use phase, the environmental impacts linked this procedure have been omitted from the analysis.

End of life

The transport distances from the place of use to the place of disposal are assumed to be 100 km.

The end of life stage is modelled according to IEC/TR 62635. The percentages for end-of-life treatments of earthing trucks are taken from IEC/TR 62635, while the data for packaging waste scenarios are provided by ISPRA.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	13/17



Environmental indicators

The following tables show the environmental impact indicators of the life cycle of a single earthing truck, as indicated by PCR EPDIItaly007 and EN 50693:2019.

The indicators are divided into the contribution of the processes to the different modules (upstream, core and downstream) and stages (manufacturing, distribution, installation, use and end-of-life).

Earthing Truck DY507

Impact category	Unit	Total	UPSTREAM	CORE	DOWNSTREAM			
			Manufacturing		Distribution	Installation	Use	End of life
GWP - fossil	kg CO ₂ eq.	8.19E+02	7.99E+02	5.37E+00	1.06E+01	5.39E-01	0.00E+00	3.12E+00
GWP - biogenic	kg CO ₂ eq.	-7.72E+00	-1.56E+01	1.16E+00	5.69E-03	6.71E+00	0.00E+00	1.76E-03
GWP - luluc	kg CO ₂ eq.	8.77E-01	8.71E-01	6.45E-04	3.73E-03	1.86E-04	0.00E+00	1.10E-03
GWP - total	kg CO ₂ eq.	8.12E+02	7.85E+02	6.53E+00	1.06E+01	7.25E+00	0.00E+00	3.13E+00
ODP	kg CFC-11 eq.	5.89E-05	5.49E-05	7.12E-07	2.42E-06	1.18E-07	0.00E+00	7.23E-07
AP	mol H ⁺ eq.	1.32E+01	1.32E+01	6.56E-03	5.39E-02	3.31E-03	0.00E+00	1.61E-02
EP - freshwater	kg PO ₄ eq.	4.63E+00	4.63E+00	1.01E-03	2.40E-03	2.24E-04	0.00E+00	7.12E-04
POCP	kg NMVOC eq.	4.63E+00	4.54E+00	5.60E-03	5.77E-02	3.77E-03	0.00E+00	1.72E-02
ADP – minerals and metals	kg Sb eq.	4.27E-01	4.26E-01	3.25E-05	2.89E-04	1.29E-05	0.00E+00	8.43E-05
ADP – fossil	MJ, net calorific value	9.59E+03	9.29E+03	8.14E+01	1.61E+02	8.23E+00	0.00E+00	4.81E+01
WDP	m ³ eq.	2.21E+02	2.08E+02	1.17E+01	4.54E-01	2.24E-02	0.00E+00	1.92E-01

GWP-fossil: Global Warming Potential fossil; GWP-biogenic: Global Warming Potential biogenic; GWP-luluc: Global Warming Potential land use and land use change; GWP-total: Global Warming Potential total; ODP: Depletion potential of the stratospheric ozone layer; AP: Acidification potential; EP-freshwater: Eutrophication potential-freshwater compartment; POCP: Formation potential of tropospheric ozone; ADP-minerals & metals: Abiotic Depletion for non-fossil resources potential; ADP-fossil: Abiotic Depletion for fossil resources potential, WDP: Water deprivation potential.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	14/17

Resource use parameters	Unit	Total	UPSTREAM	CORE	DOWNSTREAM			
			Manufacturing	Distribution	Installation	Use	End of life	
PENRE	MJ, low cal. value	9.59E+03	9.29E+03	8.14E+01	1.61E+02	8.23E+00	0.00E+00	4.81E+01
PERE	MJ, low cal. value	7.10E+00	6.80E+00	2.75E-01	1.69E-02	1.05E-03	0.00E+00	6.36E-03
PENRM	MJ, low cal. value	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERM	MJ, low cal. value	3.21E-01	3.16E-01	1.94E-04	3.41E-03	1.50E-04	0.00E+00	9.98E-04
PENRT	MJ, low cal. value	9.59E+03	9.29E+03	8.14E+01	1.61E+02	8.23E+00	0.00E+00	4.81E+01
PERT	MJ, low cal. value	1.66E+03	1.58E+03	6.80E+01	2.27E+00	1.25E-01	0.00E+00	6.71E-01
FW	m ³	1.66E+03	1.58E+03	6.80E+01	2.27E+00	1.25E-01	0.00E+00	6.71E-01
MS	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

PENRE: Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw material; PERE: Use of renewable primary energy excluding renewable primary energy resources used as raw material; PENRM: Use of non-renewable primary energy resources used as raw material; PERM: Use of renewable primary energy resources used as raw material; PENRT: Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials); PERT: Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials); FW: Net use of fresh water; MS: Use of secondary materials; RFS: Use of renewable secondary fuels, NRSF: Use of non-renewable secondary fuels.

Waste production indicators	Unit	Total	UPSTREAM	CORE	DOWNSTREAM			
			Manufacturing	Distribution	Installation	Use	End of life	
HWD	kg	4.77E+00	4.69E+00	8.52E-03	8.21E-03	6.21E-02	0.00E+00	2.56E-03
NHWD	kg	2.49E+02	2.24E+02	9.94E-01	7.69E+00	5.34E+00	0.00E+00	1.11E+01
RWD	kg	2.65E-02	2.49E-02	6.33E-05	1.10E-03	5.26E-05	0.00E+00	3.27E-04
MER	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	kg	2.36E+02	4.23E+01	0.00E+00	0.00E+00	1.64E+01	0.00E+00	1.77E+02
CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
ETE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

HWD: hazardous waste disposed; NHWD: non-hazardous waste disposed; RWD: radioactive waste disposed; MER: materials for energy recovery; MFR: material for recycling; CRU: components for reuse; ETE: exported thermal energy; EEE: exported electricity energy.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	15/17



Additional environmental information

Recyclability potential

According to the waste treatment scenario calculation in Simapro, based on the recycling rate in the technical report IEC/TR 62635 Edition 1.0 - Table D2, the following recyclability potentials were calculated.

	Earthing Truck DY507
Recyclability potential	95%

Other certifications

In 2021, the Medium Voltage Earthing Truck DY507 have been ISO 14067:2018 certified by a third party, with ID number: 1VCD500384F0001.

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	16/17



References

- LCA report 2RDA042904 - Earthing Truck DY507 - ABB, 2021
- PCR EPDItaly012 - Electronic and electrical products and systems – Switches (published: 16th March 2020)
- EN 50693:2019 - Product category rules for life cycle assessments of electronic and electrical products and systems
- PCR EPDItaly007 - Electronic and electrical products and systems (rev.2), October 2020
- IEC/TR 62635 - Guidelines for end-of-life information provided by manufacturers and recyclers and for recyclability rate calculation of electrical and electronic equipment - Edition 1.0 2012-10
- ISO 14040:2006 - Environmental management -Life cycle assessment - Principles and framework
- ISO 14044:2006 - Environmental management - Life cycle assessment - Requirements and guidelines
- ecoinvent, 2019. Swiss Centre for Life Cycle Assessment, v3.6 (www.ecoinvent.ch).
- PRé Consultants, 2020. Software SimaPro versione 9.1.1 (www.pre.nl).
- <https://www.isprambiente.gov.it/it>
- <https://www.mise.gov.it/index.php/it/>
- EPDItaly regulations rev. 5.0 (1st July 2020)

STATUS	SECURITY LEVEL	DOCUMENT ID.	REV.	LANG.	PAGE
Approved	Internal	2RDA042901	A	en	17/17