



## Environmental Product Declaration

Product: name:

**SB2DALI230**

Site Plant:

via Safforze, 8  
32100 – Belluno (BL)

**in compliance with ISO 14025 and EN 50693**


Program Operator	EPDItaly
Publisher	EPDItaly
Declaration Number	BL21620.06
EPDItaly Registration Number	EPDITALY0272
Issue Date	2022.03.14
Valid to	2027.03.14



## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

### ➡ General information

<b>EPD Holder</b>	Gavazzi Controls S.p.A., via Safforze, 8 32100 – Belluno (BL) <a href="http://www.gavazzi-automation.com">www.gavazzi-automation.com</a>
<b>Reference production site(s)</b>	Plant in Belluno: via Safforze, 8, 32100 – Belluno (BL)
<b>Field of application</b>	This document refers to a product of family <b>Fieldbus</b>
<b>Programme Operator</b>	EPDItaly - <a href="mailto:info@epditaly.it">info@epditaly.it</a>
<b>Independent verification</b>	Independent verification of declaration and data carried out according to ISO 14025:2010 <input type="checkbox"/> _Internal <input checked="" type="checkbox"/> _External  3rd party verification conducted by: ICMQ SpA, via De Castillia, 10 20124 – _Milano ( <a href="http://www.icmq.it">www.icmq.it</a> ), Accredited by Accredia
<b>CPC code</b>	4621 "Electricity distribution or control apparatus"
<b>Contact</b>	<u>Alberto Mambrini</u> , LCA Process Owner in Carlo Gavazzi Controls SpA
<b>Technical support</b>	 <b>Aequilibria Srl - SB</b> P.le Martiri delle Foibe, 5 30175 – Marghera Venezia (VE) - ITALIA
<b>Comparability</b>	Environmental declarations published within the same product category, but coming from different programmes, may be not comparable. In particular, EPD of similar products may be not comparable if not compliant to the reference norms
<b>Responsibility</b>	Carlo Gavazzi Controls S.p.A. relieves EPDItaly from any non-compliance with environmental legislation. The holder of the declaration will be responsible for the information and supporting evidence; EPDItaly declines all responsibility for the manufacturer's information, data and results of the life cycle assessment.
<b>Reference documents</b>	This declaration was developed according to the EPDItaly Regulation; the Regulation (Rev.5 of 01/07/2020), available at <a href="http://www.epditaly.it">www.epditaly.it</a> .

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

	The standard EN 50693:2019 represents the reference for the PCR "Electronic and electrical products and systems" (PCR EPDItaly007).
<b>PCR – Product Category Rules</b>	<b>Core-PCR:</b> EPDITALY007 "Electronic and electrical product and systems" Rev. 2 of 21/10/2020
<b>Document date and revision</b>	Dec 20 2021, rev. 0

Table 1. EPD general information

# Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

## Introduction

This document represents the EPD study conducted for the product SB2DALI230, manufactured by Carlo Gavazzi Controls S.p.A., in conformity to the Program EPDIItaly and the relevant Regulation. The Regulation was developed according to ISO 14025 and aims to provide a tool to develop, verify and publish the product EPDs.

This study was done according to the PCR EPDIItaly007 (*PCR for electronic and electrical products and systems*), that identifies and documents:

- The target and field of application of LCA-based info for the product category;
- The rules for productions of additional environmental info;
- The stages of LCA to be included;
- The parameters to be considered and the way to collect and communicate them in a report.

## Information on the manufacturer and environmental policy

Carlo Gavazzi Controls SpA develops, produces, sells monitoring relays, timers, energy management systems field bus systems, providing solutions for residential, commercial, industrial automation within the low-voltage installations.

Carlo Gavazzi products are sold in Europe, North-America, Asia-pacific area, through a network of more than 20 own sales companies and approx 60 independent national distributors. Carlo Gavazzi Controls has a production plant in Belluno (via Safforze 8, 32100 – Belluno), involved in this study.

Carlo Gavazzi is certified ISO9001 (from 1997) and ISO14001 (from 2009). Both certifications are issued by accredited Bodies.

Carlo Gavazzi Controls commits to reduce continuously the environmental impact of its products, through the implementing of the ISO14001 certified Environmental Management System and of a design process aware of the environment, based on the principles of norm EN 62430.

The environmental statements have been evaluated by using a qualitative approach on the environment-aware design process.

# Environmental Product Declaration

## SB2DALI230 SMART-DUPLINE® DALI MASTER

### Product information

The product here analyzed is the device **SB2DALI230**, belonging to the family Fieldbus, with rated power consumption 9W, weight 160 g, including packaging and instructions.

According to the reference PCR, According to the reference PCR, the functional unit has been defined as a device, **characterized by a power consumption of 9W during a RSL (Reference Service Life) of 10 years, including its packaging, working continuously during its whole service life.**

It is a device used for fieldbus applications, compliant to the EMC Directive, LVD Directive, RoHS Directive.

Assembling, testing and packing is carried out at the production plant of Carlo Gavazzi Controls. During the use stage the product doesn't require any specific maintenance and it is considered turned on for the whole service life estimated in 10 years, with a rated power consumption of 9W when supplied at the rated voltage 110-240Vac.

The finished product is sent from the production plant to the logistic centers for following distribution.


<b>Product family</b>	Fieldbus	
<b>Product name</b>	SB2DALI230, SMART-DUPLINE® DALI MASTER	
<b>Technical data</b>	Power consumption: 9W @ 110-240Vac Frequency: 50-60Hz Weight: 102,7 (excluding packaging) Reference Service Life (RSL):10 years	
<b>Packaging</b>	Weight: 57,3g Material: cardboard, paper	

Table 2. Information relevant to the product SB2DALI230

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

**➡ Materials and substances contained in the product**

The material declaration is done according to EN IEC 62474.

The product complies with the RoHS Directive 2011/65/EU and amendment 2015/863/EU.

The product doesn't contain batteries.

Any percentage of recycled material is unknown.

The percentages of each raw material, as well as the total weight including packaging, are indicated in table 3.

Total weight	<b>160g</b> (including packaging)
--------------	-----------------------------------

Raw material category	SCLAM	SCLAM description	% SCLAM on total weight	% category on total weight
<b>PCB</b>	PCB-SEM	Printed circuit boards one/two layers	0,50%	12,12%
	PCB-SEM	Printed circuit boards one/two layers	2,44%	
	PCB-SEM	Printed circuit boards one/two layers	3,95%	
	PCB-SEM	Printed circuit boards one/two layers	5,23%	
<b>Electronic components</b>	CCERP	PTH - Ceramic capacitors	0,972%	13,01%
	CCERS	SMD - Ceramic capacitors	0,001%	
	CCERS	SMD - Ceramic capacitors	0,072%	
	CCERS	SMD - Ceramic capacitors	0,034%	
	CCERS	SMD - Ceramic capacitors	0,094%	
	CCERS	SMD - Ceramic capacitors	0,143%	
	CELEP	PTH - Electrolytic capacitors	1,614%	
	CELEP	PTH - Electrolytic capacitors	1,519%	
	CFLMP	PTH - Film capacitors	0,578%	
	CNTRS	Connectors	0,247%	
	CNTRS	Connectors	0,355%	
	CNTRS	Connectors	0,557%	
	CNTRS	Connectors	0,663%	
	CNTRS	Connectors	0,141%	
	CNTRS	Connectors	0,206%	
	CTANS	SMD - Tantalum capacitors	0,146%	
	DDPTH	PTH - Diodes, zeners, leds, Transils, rectifier bridges	0,338%	
	DDPTH	PTH - Diodes, zeners, leds, Transils, rectifier bridges	0,269%	

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,004%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,003%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,005%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,011%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,018%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,019%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,042%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,066%
DDSMD	SMD - Diodes, zeners, leds, Transils, rectifier bridges	0,070%
ICDIL	DIL - Integrated circuits	0,325%
ICSMD	SMD - Integrated circuits	0,009%
ICSMD	SMD - Integrated circuits	0,038%
ICSMD	SMD - Integrated circuits	0,070%
ICSMD	SMD - Integrated circuits	0,269%
INDCP	PTH - Inductors	0,131%
INDCP	PTH - Inductors	0,269%
MICRO	Microprocessors	0,150%
RESMD	SMD Resistors	0,000%
RESMD	SMD Resistors	0,000%
RESMD	SMD Resistors	0,010%
RESMD	SMD Resistors	0,065%
RESMD	SMD Resistors	0,007%
RESMD	SMD Resistors	0,010%
RESMD	SMD Resistors	0,048%
RESMD	SMD Resistors	0,213%
RESTD	Resistors	0,100%
RESTD	Resistors	0,103%
TRPTH	PTH - Transistors and mosfets	1,172%
TRSMD	SMD - Transistors and mosfets	0,005%
TRSMD	SMD - Transistors and mosfets	0,020%
TRSMD	SMD - Transistors and mosfets	0,014%
TRSMD	SMD - Transistors and mosfets	0,053%
VARIP	PTH - Varistors	1,746%
PTTCP-PO	Potting compounds polyurethane	0,13%

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

<b>Specific product SCLAM</b>	TRAFO	Transformers	5,62%	5,75%
<b>Cables</b>	-	-	-	
<b>Small metal parts</b>	MECUS-OT	Custom metal parts brass	1,71%	6,59%
	MESTD-RA	Standard metal parts copper	3,06%	
	MESTD-ST	Standard metal parts steel	0,43%	
	MESTD-ST	Standard metal parts steel	1,39%	
<b>Plastic materials</b>	LAFRO-PL	Frontal labels (polyester)	0,18%	26,74%
	LAPAC	Packaging labels	0,95%	
	PLCUS-HO	Custom parts Hostaform	0,53%	
	PLCUS-NO	Custom parts Noryl	0,47%	
	PLCUS-NO	Custom parts Noryl	0,30%	
	PLCUS-NO	Custom parts Noryl	0,30%	
	PLCUS-NO	Custom parts Noryl	0,58%	
	PLCUS-NO	Custom parts Noryl	11,15%	
	PLCUS-NO	Custom parts Noryl	5,70%	
	PLCUS-NO	Custom parts Noryl	6,41%	
<b>Paper packaging</b>	PLCUS-PC	Custom plastic parts polycarbonate	0,17%	35,79%
	BOXES	Carton boxes	4,43%	
	BOXES	Carton boxes	23,85%	
	SHEET	Instruction sheets/ manuals	7,51%	

Table 3. Material categories (SCLAM) percentages for product SB2DALI230



# Environmental Product Declaration

## SB2DALI230 SMART-DUPLINE® DALI MASTER

### Information relevant to the study

<b>System boundaries</b>	The system boundaries of this study is considered “ <b>cradle-to-grave</b> ”
<b>Geographic validity</b>	Global
<b>Reference year</b>	2019
<b>Reference tool</b>	This EPD was generated by using data obtained automatically by the certified Excel tool “LCA tool_dati 2019_GAV – rev1” of 23/06/2021

Table 4. Information relevant to the study

The evaluation of all environmental impacts above mentioned is based on the whole life-cycle of the analyzed product: production, distribution, installation, use and end-of-life.

Following is a description of elements and processes taken into consideration, to evaluate the impacts for each stage:

<b>Production</b>	<ul style="list-style-type: none"> <li>raw materials of product and packaging (primary and secondary), auxiliary materials and relevant transportation.</li> <li>production and working processes, that cause energy and water consumption, emissions in air, waste generated during production               <ul style="list-style-type: none"> <li>Dataset electricity: <i>Electrical Energy– medium RESIDUAL MIX (Ecoinvent 3.6)</i></li> </ul> </li> </ul>																					
<b>Distribution</b>	<ul style="list-style-type: none"> <li>transportation from the production plant to the logistic centers</li> </ul> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr style="background-color: #FFD700;"> <th colspan="3">DISTRIBUTION OF FINISHED PRODUCT (CdD)</th> </tr> <tr style="background-color: #FFF2CC;"> <th>Logistic center</th> <th>% of distribution</th> <th>Further distribution at continental level?</th> </tr> </thead> <tbody> <tr> <td>CGC-CdD Italy</td> <td>84,2%</td> <td>No</td> </tr> <tr> <td>CGC-CdD Spain</td> <td></td> <td></td> </tr> <tr> <td>CGC-CdD USA</td> <td></td> <td></td> </tr> <tr> <td>CGC-CdD Canada</td> <td></td> <td></td> </tr> <tr> <td>CGC-CdD Singapore</td> <td>15,8%</td> <td>No</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>disposal of secondary packaging</li> </ul>	DISTRIBUTION OF FINISHED PRODUCT (CdD)			Logistic center	% of distribution	Further distribution at continental level?	CGC-CdD Italy	84,2%	No	CGC-CdD Spain			CGC-CdD USA			CGC-CdD Canada			CGC-CdD Singapore	15,8%	No
DISTRIBUTION OF FINISHED PRODUCT (CdD)																						
Logistic center	% of distribution	Further distribution at continental level?																				
CGC-CdD Italy	84,2%	No																				
CGC-CdD Spain																						
CGC-CdD USA																						
CGC-CdD Canada																						
CGC-CdD Singapore	15,8%	No																				

**Environmental Product Declaration**  
 SB2DALI230 SMART-DUPLINE® DALI MASTER

<b>Installation</b>	•disposal of primary packaging.
<b>Use and maintenance</b>	• Product category: Fieldbus • use scenario: 10 years of service life, 100% working at rated conditions, rated power consumption 9W.
<b>End of life</b>	•Scenario of end-of-life of the device (WEEE)

*Table 5. Processes considered during the various stages of the study*

The LCA study has been conducted according to the norms UNI EN ISO 14040/14044, following the guidelines of EN 50693:2019.

Software used for the impact evaluation: SimaPro 9.1.1.1; database Ecoinvent 3.6.

The calculations of impacts refer to refer to the method CML baseline and IPCC, for the impact category relevant to the climate change.

Specific site-data were used for all the following processes:

- production and transportation of raw materials, auxiliary materials, packaging materials;
- manufacturing processes, energy consumption of the plant, air emissions and waste;
- weight and power consumption of the device;
- transportation to the logistic center.

Generic data were used for:

- recycle rates, energy recovery and disposal for the materials of packaging (primary and secondary) and for WEEE (data at global level).

The default scenarios described in the PCR007 were used for:

- transportation to the sales point: scenario of intercontinental and local transportation;
- Life-time (RLS) of the device: 10 years.

**➡ Evaluation of the environmental impact**

The potential environmental impacts evaluated through the LCA of the device SB2DALI230 are reported in table 6 below. The impacts were calculated by using the software SimaPro Developer 9.1.1.1 and database Ecoinvent 3.6.

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

ENVIRONMENTAL IMPACT								
Impact category	Unit	PRODUCTION		DISTRIBUTION	INSTALLATION	USE AND MAINTAINANCE	END-OF-LIFE	TOTAL
		UPSTREAM module	CORE module	DOWNSTREAM module				
GWP TOT (Global Warming Potential)	kg CO <sub>2</sub> eq	5,16E+00	1,85E+00	1,85E-01	1,87E-03	3,34E+02	2,85E-02	<b>341,60</b>
GWP - fossil	kg CO <sub>2</sub> eq	5,14E+00	1,85E+00	1,85E-01	1,87E-03	3,31E+02	2,84E-02	<b>337,83</b>
GWP - biogenic	kg CO <sub>2</sub> eq	1,31E-02	4,73E-03	3,25E-05	4,05E-07	3,69E+00	1,17E-05	<b>3,70</b>
GWP Luluc (GWP land use and land use change)	kg CO <sub>2</sub> eq	1,14E-02	4,26E-04	3,53E-05	3,41E-07	5,75E-02	9,01E-06	<b>0,07</b>
ODP (Ozone depletion)	kg CFC <sub>11</sub> eq	4,47E-07	2,99E-07	4,14E-08	2,13E-10	4,12E-05	6,47E-10	<b>4,20E-05</b>
AP (Acidification)	mol H <sup>+</sup> eq	5,17E-02	8,02E-03	9,35E-04	5,92E-06	1,59E+00	4,07E-05	<b>1,65</b>
EP (Eutrophication, freshwater)	kg P eq	7,86E-03	4,56E-04	7,75E-06	1,57E-07	8,29E-02	2,67E-06	<b>0,09</b>
POCP (Photochemical ozone formation)	kg NMVOC eq	2,68E-02	4,10E-03	9,70E-04	6,56E-06	7,07E-01	3,14E-05	<b>0,74</b>
ADPE (Resource use, minerals and metals)	kg Sb eq	2,95E-03	7,53E-06	2,27E-06	2,16E-08	2,40E-03	1,80E-07	<b>5,37E-03</b>
ADPF (Resource use, fossils)	MJ	6,93E+01	3,05E+01	2,65E+00	1,46E-02	5,10E+03	8,62E-02	<b>5204,45</b>
WDP (Water use)	m <sup>3</sup> depriv.	1,43E+00	4,47E-01	4,51E-03	2,24E-04	1,67E+02	1,18E-03	<b>168,84</b>

Table 6. Results of various environmental impact categories for device SB2DALI230

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

USE OF RESOURCES								
Impact category	Unit	PRODUCTION		DISTRIBUTION	INSTALLATION	USE AND MAINTAINANCE	END OF LIFE	TOTAL
		UPSTREAM module	CORE module	DOWNSTREAM module				
PENRE	MJ	7,28E+01	3,29E+01	2,81E+00	1,56E-02	5,52E+03	9,17E-02	<b>5632,99</b>
PENRM	MJ	1,13E+00	7,60E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	<b>1,21</b>
PENRT	MJ	7,25E+01	3,30E+01	2,81E+00	1,56E-02	5,52E+03	9,17E-02	<b>5632,91</b>
PERE	MJ	6,85E+00	3,96E+00	2,15E-02	1,85E-04	1,29E+03	7,06E-03	<b>1301,67</b>
PERM	MJ	3,39E+00	5,86E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	<b>3,98</b>
PERT	MJ	7,79E+00	4,55E+00	2,15E-02	1,85E-04	1,29E+03	7,06E-03	<b>1303,19</b>
FW (Net use of fresh water)	m <sup>3</sup>	5,05E-02	1,57E-02	1,74E-04	6,26E-06	4,49E+00	4,69E-05	<b>4,56</b>
MS (use of secondary materials)	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	<b>0,00</b>
RSF (use of renewable secondary fuels)	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	<b>0,00</b>
NRSF (Use of non-renewable secondary fuels)	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	<b>0,00</b>

Table 7. Environmental impacts referred to use of resources for device SB2DALI230

Legend: **PENRE** = Use of primary non-renewable energy resources, excluding primary non-renewable energy resources used as raw materials; **PENRM** = Use of primary non-renewable energy resources as raw materials; **PENRT** = Total use of primary non-renewable energy resources; **PERE** = Use of primary renewable energy resources, excluding primary renewable energy resources used as raw materials; **PERM** = Use of primary renewable energy resources as raw materials; **PERT** = Total use of primary renewable energy resources.

## Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

WASTE PRODUCTION								
Impact category	Unit	PRODUCTION		DISTRIBUTION	INSTALLATION	USE AND MAINTAINANCE	END OF LIFE	TOTAL
		UPSTREAM module	CORE module	DOWNSTREAM module				
Hazardous waste disposal (HWD)	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	8,51E-02	8,51E-02
Non-hazardous waste disposal (NHWD)	kg	0,00E+00	0,00E+00	1,86E-02	1,63E-02	0,00E+00	0,00E+00	3,49E-02
Radioactive waste disposal (RWD)	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for energy recovery (MER)	kg	0,00E+00	0,00E+00	3,15E-03	1,98E-03	0,00E+00	0,00E+00	5,12E-03
Materials for recycling (MFR)	kg	0,00E+00	1,33E-02	1,94E-02	3,70E-02	0,00E+00	1,79E-02	8,77E-02
Components for reuse (CRU)	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
ETE (exported thermal energy)	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE (exported electricity energy)	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

Table 8. Environmental impacts referred to waste, for product SB2DALI230

# Environmental Product Declaration

SB2DALI230 SMART-DUPLINE® DALI MASTER

---

## References

- ❖ ISO 14040:2006 Environmental management - Life cycle assessment - Principles and framework
- ❖ ISO 14044:2018 Environmental management - Life cycle assessment - Requirements and guidelines
- ❖ ISO 14020:2000 Environmental labels and declarations - General principles
- ❖ UNI EN ISO 14025:2010, Etichette e dichiarazioni ambientali - Dichiarazioni ambientali di Tipo III - Principi e procedure
- ❖ EN 50693:2019 Product category rules for life cycle assessments of electronic and electrical products and systems
- ❖ EPDItaly Regulation, Rev. 5 of 01/07/2020
- ❖ Core-PCR: EPDITALY007 " Electronic and electrical product and systems" Rev. 2 del 21/10/2020